

PGDQ2.MH14339 - Marking and Labeling Systems - Component

Marking and Labeling Systems - Component

[See General Information for Marking and Labeling Systems - Component](#)

AMERICAN NAMEPLATE CO

4501 S KILDARE
CHICAGO, IL 60632 USA

MH14339

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels.						
Americal FS						
	Alkyd paint	150	-	X	-	C
	Aluminized steel	150	-	X	-	C
	Aluminum	150	-	X	-	-
	Galvanized steel	150	-	X	-	C
	Stainless steel	150	-	X	-	C
Americal ML						
	Acrylonitrile butadiene styrene	80	-40	X	-	-
	Alkyd paint	80	-40	X	-	C
	Aluminized steel	80	-40	X	-	C
	Aluminum	80	-40	X	-	C
	Epoxy	80	-40	X	-	-
	Galvanized steel	80	-40	X	-	C
	Nylon - Polyamide	80	-40	X	-	-
	Polyester paint	80	-40	X	-	-
	Polyphenylene oxide/ether	80	-40	X	-	-
	Polycarbonate	60	-40	X	-	-
	Polyurethane paint	60	-40	X	-	-
	Porcelain	60	-40	X	-	-

	Stainless steel	60	-40	X	-	C
	Polyethylene terephthalate	40	-40	X	-	-
Americal OF						
	Alkyd paint	175	-40	X	X	-
	Aluminum	175	-40	X	X	-
	Epoxy paint	175	-40	X	X	-
	Galvanized steel	175	-40	X	X	-
	Porcelain	175	-40	X	X	-
	Stainless steel	175	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
Americal OF4						
	Alkyd paint	150	-40	X	X	-
	Aluminum	150	-40	X	X	-
	Galvanized steel	150	-40	X	X	-
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	Nylon - Polyamide	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
Americal OF9						
	Alkyd paint	125	-40	X	X	-
	Aluminum	125	-40	X	X	-
	Galvanized steel	125	-40	X	X	-
	Porcelain	125	-40	X	X	-
	Stainless steel	125	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polystyrene	80	-40	X	X	-

Americal P						
	Alkyd paint	150	-40	X	-	O, C
	Aluminized steel	150	-40	X	-	C
	Aluminum	150	-40	X	-	O
	Galvanized steel	150	-40	X	-	O, C
	Anodized aluminum	125	-40	X	-	O
	Melamine	100	-29	X	-	O
	Nylon - Polyamide	100	-29	X	-	O
	Phenolic - Phenol Formaldehyde	100	-29	X	-	O
	Polycarbonate	100	-29	X	-	O
	Polyester paint	100	-29	X	-	O
	Porcelain	100	-29	X	-	O
	Stainless steel	100	-29	X	-	O, C
	Acrylic paint	80	-40	X	-	O
	Acrylonitrile butadiene styrene	80	-40	X	-	O
	Polypropylene	80	-	X	-	O
	Polystyrene	80	-29	X	-	O
	Unsaturated polyester - thermoset	80	-40	X	-	O
Americal PH						
	Alkyd paint	150	-40	X	-	O, C
	Aluminized steel	150	-40	X	-	C
	Aluminum	150	-40	X	-	O
	Anodized aluminum	150	-40	X	-	O
	Galvanized steel	150	-40	X	-	O, C
	Polyester paint	150	-29	X	-	O
	Stainless steel	150	-29	X	-	O, C
	Melamine	100	-29	X	-	O
	Nylon - Polyamide	100	-29	X	-	O
	Phenolic - Phenol Formaldehyde	100	-29	X	-	O
	Polycarbonate	100	-29	X	-	O
	Porcelain	100	-29	X	-	O

	Acrylic paint	80	-40	X	-	O
	Acrylonitrile butadiene styrene	80	-40	X	-	O
	Polypropylene	80	-	X	-	O
	Polystyrene	80	-29	X	-	O
	Unsaturated polyester - thermoset	80	-40	X	-	O
Americal V						
	Acrylic paint	80	-29	X	-	O
	Acrylonitrile butadiene styrene	80	-29	X	-	O
	Alkyd paint	80	-29	X	-	O, C
	Aluminized steel	80	-29	X	-	C
	Galvanized steel	80	-29	X	-	C
	Stainless steel	80	-29	X	-	O, C
	Unsaturated polyester - thermoset	80	-29	X	-	O
	Aluminum	60	-29	X	-	O
	Polypropylene	40	-29	X	-	O

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

C - Occasional exposure to Cooking Oil (room temp).

O - Occasional exposure to Lubricating Oil.

Marking: Company name and model designation.

Last Updated on 2016-04-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"